


CARPET TILES MAGIC

CARPET TILES
50 X 50cm

Phone: [+971554722980](tel:+971554722980)
Email: info@fixitdesign.ae
Web: info@fixitdesign.ae




Petrol
878



Light Brown
848



Carbon
378




Savanna
568



Dark Grey
978



Ocean
858



Blue
358



Light Grey
678



Diesel
278


MAGIC

Product Specification:


Style Construction	:	Magic
Pile Fiber Composition	:	Loop pile full repeat scroll (FRS)
Yarn Type	:	100% Olefin Polypropylene
Dye Metho Gauge	:	BCF
Pile Height Pile Weight	:	Solution Dyed
Total Weight	:	1/2"
Primary Backing	:	3.00mm / 4.00mm
Secondary Backing	:	800g/m ²
Total Thickness	:	5065g/m ²
Number of Tufts Tile Size	:	PES/PA Fleece (Non woven Textile)
Area of use Packing	:	PVC reinforced by Glass Fiber
	:	7.00mm
	:	222780/m ² (Approx)
	:	50 x 50cm
	:	Commercial
	:	20pcs/carton (5m ²)

Performance Specification:

Flammability	:	ASTM D-2859/FFI-70/16CFR
Smoke Density	:	1630 Pass 8/8
Static Prepensity	:	ASTM E662 Less than 450
Colour Fastness	:	AATCC - 134 under 3.5KV
Soiling Propensity	:	5:5 on Gray Scale
Dimensional Stability	:	AATCC123 Grey Scale 5 DXN 54318 6.20



Quarter
Turn



Ashilar



Sound
Insulation




Heat
Insulation



Anti-static



Colorfas
t



Wearpro
of



Anti-
flammability

Terms and Conditions: Specifications are subject to manufacturing tolerances and maybe changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Messara Trading Standard Terms and Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification.

Disclaimer: This Brochure is presented for informational purposes only. Every effort is made to ensure that carpet images are of an accurate representation of the product. However, they are for illustrative purposes only and colour variations may occur in actual product, and between die series. Please note that lineal patterns when installed directional, may produce an undesired effect when lines of the same colour meet of two edges. Installers need to monitor this during installations and reposition tiles where appropriate. Patterns that are random in nature may contain additional colour ways to the ones displayed on the samples. Please consult your commercial sales consultant for further informations.