



A world
of colours
to energize
your sport

HETEROGENEOUS VINYL

**Multigym
450**

HETEROGENEOUS VINYL

Multigym 450



5203 079 / 5203 096

Red




5203 078 / 5203 099

Orange



5203 081

Soft Green




5203 098

Apple Green

HETEROGENEOUS VINYL

Multigym 450



5203 080 / 5203 097

Blue



 5203 057

Noyer Brown



 5203 047

Antik Oak Beige

HETEROGENEOUS VINYL

Multigym 450

Specification

Multigym 450



CERTIFICATION & CLASSIFICATION

STANDARDS

Multigym 450

Vinyl floor	EN ISO 26986	
Covering Classes of Use	EN ISO 10874	23 31

Impact Sound Absorption	EN ISO 717-2	20 dB
-------------------------	--------------	-------

TECHNICAL CHARACTERISTICS

STANDARDS

Multigym 450

Total Thickness	EN ISO 24346	4.50 mm
Wear Layer Thickness	EN ISO 24340	0.30 mm
Residual Indentation	EN ISO 24343-1	≤ 0.35
Weight	EN ISO 23997	3,000 kg/m ²
Wear Layer Binder Content	ISO 11638	Type 1
Roll Dimensions	EN ISO 24341	Roll Length : 19 m Roll Width : 4 m
Castor Chair	ISO 4918	OK

TECHNICAL PERFORMANCES

STANDARDS

Multigym 450

Slip Resistance	EN 13893	μ ≥ 0.30
Fire Classification	DIN 51130	R10
	EN 13501-1	CfL-S1
Static Electrical Propensity	EN 1815	≤ 2 kV
Chemical Resistance	EN ISO 26987	Not Affected
Dimensional Stability	EN ISO 23999	≤ 0.40%
Light Fastness	EN ISO 105 BO2	≥ 6

Thermal resistance for underfloor heating ISO 10456 - EN 12524-1

The above information is subject to modification for the benefit of further improvement. (05714).
Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

PHTHALATE FREE Technology

*except recycled content

<100 μg/m³*

Better Indoor Air Quality

*TVOC AT 28 DAYS

100 %

Recyclable

Multigym 450

No. 0131-0009-DoP-2014-12
<http://www.home.tarkett.com>

Manufactured by:
Tarkett GDL S.A.
2 Op der Sang, L-9779 Lentzweiler

EN 14041 : 2004

ÉMISSIONS DANS L'AIR INTÉRIEUR*

A+

A+ A B C