





ST-22 Yellow Brown



ST-68 Red Brown



ST-31 Co ee Brown



ST-14 Grey Red

Quality Parameters:

CARPET TILE STAR

Product Form :Tile

Product Dimensions :500 x 500mm **Product**

:Tufted loop pile Construction : 100% BCF

Surface Yarn Polypropylene

Pile Dye Method : Solution Dyed Weight Stitches :500g/m

Primary Backing : 48 per dm Secondary Backing : Polypropylene

Total thickness Pile : Bitumen

Height :6mm Total Weight :3mm

Packaging : about 3160g/m :6 sqm/carton

PERFORMANCE SPECIFICATION

fastness to light

Hot metal nut BS < 75mm (Medium 4790:1987 Smoke Density Radius) ASTM-E-662 Color <=450 DMC Pass Grade 4 Pass fastness to water Color

Color fastness to rubbing

Malaber of binding sites per length or width of floor covering: 32/39

Carpets: Cleaning of: hot water extraction method 4.



Retardant-does not contribute to the start or spread of fire.



medium contract use: o ces, shops, schools, hospitals and other public areas.



Suitable for areas castor chairs are used.



Suitable for use in rooms where personal computers are installed.



Permanently Antistaticelectrostatic shock is reduced to a minimum.

