

Structured Loop Carpet Tiles 50 X 50 cm



Phone: <u>+971554722980</u> Email: <u>info@fixitdesign.ae</u>

Web:info@fixitdesign.ae





Green 666



Blue 556





Dark Grey 676



Brown 346





Beige 046



Red 626







## **Specification:**

Construction Structued Loop

Yarn/Fibre Dye 100% Olefin

Method Pile Weight Solution Dyed

Pile Height Gauge 700 g/m<sup>2</sup> (+/-5%)

Stitches/ 10cm Tile 3.00mm / 6.00mm

Size Backing 1/10TH

Total Thickness Total 47.0

Weight Tuft Density  $50 \times 50 \text{cm}$ 

**Dimensional Stability** Glass fiber Reinforced PVC

Electrostatic 7.5mm

Propensity Fire Rating 5.0kg/m<sup>2</sup> (+/-5%)

ISO 9239.1 Installation 185650/m<sup>2</sup>

Method DXN 54318 6.20

AATCC - 134 < 3.5KV

**ECO-800 Pressure Sensitive Low** 

VOC

Quarter Turn (Preferred)



Quarter







Sound Insulation



Heat Insulation



Anti-static



Colorfast



Wearproof



flammability

Terms and Conditions: Speci cations are subject to manufacturing tolerances and maybe changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Messara Trading Standard Terms and Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clari cation.

Disclaimer: This Brochure is presented for informational purposes only. Every effort is made to ensure that carpet images are of an accurate representation of the product. However, they are for illustrative purposes only and colour variations may occur in actual product, and between die series. Please note that lineal patterns when installed directional, may produce an undesired effect when lines of the same colour meet of two edges. Installers need to monitor this during installations and reposition tiles where appropriate. Patterns that are random in nature may contain additional colour ways to the ones displayed on the samples. Please consult your commercial sales consultant for further informations.